





SPRAY GUN

Airless + Air

Series AA



Dimensions	251 x 177 x 49 mm
Working humidity	35 - 90 %
Storage temperature	10 - 40 °C
Relative humidity storage	35 - 90 %
Temperatura di trasporto	10 - 40 °C
Transport temperature	35 - 90 %
ATEX Marking	Ex II 2G T60°C X
Compressed air quality ISO 8573-1	1:4:1
Spray width SB 50%	50 - 510 mm
Spraying distance	250 - 300 mm
Operation	manual
Pressure	250,0 bar
Connection pressure	3626,0 psi
Explosion Pressure	1000 bar
Viscosity	< 4000 mPa.s
Average working temperature	< 60 °C
Output connection	1/4" NPSM / M16x1,5
Average flow, max.	180 - 3500 ml/min
Material in contact with the product	Stainless steel
Seal material	PTFE



Medium pressure spray gun with airless atomization and additional air for fan adjustment and uniformity of spraying. Practical, handy, soft in product distension. Ideal for use with pressures from 80 to 150 bar.

Concessionário:

WWW.CMSPRAY.IT

CMSPRAY@CMSPRAY.IT

Tel. +39(0)422 398768

Fax +39(0)422 398594

Carbonera (TV) ITALY